

XS TRACK M19A/M190/M19T

Xs track is as easy to install as a surface system, but it looks like a trimless track due to its small size and its geometric simplicity.

PRODUCT RANGE

XS TRACK M19A/M190/M19T system

TYPE

XS TRACK M19A



XS TRACK M190



XS TRACK M19T



MOUNTING

SURFACE



SUSPENDED



TRIMLESS RECESSED



INSETS

IT28



IT30



LO35



LO30



GRILLE FOLD



GRILLE S



GRILLE R



LINEAR LIGHT



XS TRACK M19A surface



SIZE(mm)

1000x19x10
2000x19x10
3000x19x10




110x19x10



150x11x7




86x86x7



29x29x10




160x75x7



39x29x10




160x160x7



39x39x10



218x11x7



26x26x19



19x12x10



SIZE(mm)	PRODUCT NAME	ORDER CODE
1000x19x10	Track rail	10.M19A10000
2000x19x10	Track rail	10.M19A20000
3000x19x10	Track rail	10.M19A30000
110x19x10	Power feeder unit	10.M19L01000
150x11x7	Linear(connector)	10.M19L02000
86x86x7	L-connector	10.M19L03000
29x29x10	L-connector fixing part	10.M19L03001
160x75x7	T-connector	10.M19L04000
39x29x10	T-connector fixing part	10.M19L04001
160x160x7	X-connector	10.M19L05000
39x39x10	X-connector fixing part	10.M19L05001
218x11x7	Linear flexible	10.M19L06000
26x26x19	Vertical corner*v90° installation fixing part	10.M19L06001
19x12x10	End caps	10.M19L07000

MATERIAL COLOUR | BK ■ |

MATERIAL | AL ■ |



XS TRACK M19O suspended



SIZE(mm)	PRODUCT NAME	ORDER CODE
1000x22x22	Track rail	10.M19O10000
2000x22x22	Track rail	10.M19O20000
3000x22x22	Track rail	10.M19O30000











XS TRACK M19T trimless recessed









SIZE(mm)	PRODUCT NAME	ORDER CODE
1000x40x11	Track rail	10.M19T10000
2000x40x11	Track rail	10.M19T20000
3000x40x11	Track rail	10.M19T30000



	150x11x7	Linear(connector)	10.M19L02000
	86x86x7	L-connector	10.M19L03000
	160x75x7	T-connector	10.M19L04000
	160x160x7	X-connector	10.M19L05000
	218x11x7	Linear flexible	10.M19L06000
	2000x15	Pendant kit	10.M19L08000
	2000x15	Pendant kit	10.M19L09000
	22x22x12	End caps	10.M19L10000

MATERIAL COLOUR | BK ■ | MATERIAL | AL □ |

	110x19x10	Power feeder unit	10.M19L01000
	150x11x7	Linear(connector)	10.M19L02000
	86x86x7	L-connector	10.M19L03000
	160x75x7	T-connector	10.M19L04000
	160x160x7	X-connector	10.M19L05000
	218x11x7	Linear flexible	10.M19L06000

MATERIAL COLOUR | BK ■ | MATERIAL | AL □ |

IT28



XS TRACK M19A/M19O/M19T spotlight




IT28	10.002A01000
Power	5.3W
Beam angle	15°/24°/36°/50°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	87lm/W
Color rendering index	≥90
Operating temperature	-25-50
Rated life hours	35,000-50,000H LM80
LED chip	COB



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL

IT30



XS TRACK M19A/M19O/M19T spotlight




IT30	10.003A01000
Power	5.3W
Beam angle	18-31°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	36lm/W
Color rendering index	≥90
Operating temperature	-25-50
Rated life hours	35,000-50,000H LM80
LED chip	COB



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL



LO35



XS TRACK M19A/M19O/M19T spotlight




LO35	10.004A01000
Power	4.5W
Beam angle	15°/24°/36°/50°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	66lm/W
Color rendering index	≥90
Operating temperature	-25-50
Rated life hours	35,000-50,000H LM80
LED chip	COB



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL

LO30

XS TRACK M19A/M190/M19T spotlight




LO30	10.005A01000
Power	5.3W
Beam angle	15°/24°/36°/50°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	87lm/W
Color rendering index	≥90
Operating temperature	-25-50
Rated life hours	35,000-50,000H LM80
LED chip	COB



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL □



GRILLE FOLD



XS TRACK M19A/M190/M19T grille




GRILLE FOLD		10.007A09000
Power		8.5W
Beam angle		20°/25°/38°/60°
Color temperature		2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency		73lm/W
Color rendering index		≥90
Operating temperature		-25-50
Rated life hours		35,000-50,000H LM80
LED chip		COB



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL

GRILLER



XS TRACK M19A/M190/M19T grille




GRILLE R	10.009A18000	
Power	8.5W	
Beam angle	20°/25°/38°/60°	
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K	
Light efficiency	79lm/W	
Color rendering index	≥90	
Operating temperature	-25~50	
Rated life hours	35,000-50,000H LM80	
LED chip	COB	



OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □ | MATERIAL | AL