



SCOPE PRO





| SCOPE PRO | 030833A01(Recessed) | |
|-----------------------|-------------------------------|--|
| Power | 20W | |
| Beam angle | 15°/23°/36° | |
| Color temperature | 2700K/3000K/3500K/4000K/5000K | |
| Light efficiency | 75lm/W | |
| Color rendering index | ≥90 | |
| Operating temperature | -25- +50 | |
| Rated life hours | 35,000-50,000H | |
| LED chip | COB | |



| SCOPE PRO | 030833A02(Recessed) | |
|-----------------------|-------------------------------|--|
| Power | 40W | |
| Beam angle | 15°/23°/36° | |
| Color temperature | 2700K/3000K/3500K/4000K/5000K | |
| Light efficiency | 77lm/W | |
| Color rendering index | ≥90 | |
| Operating temperature | -25- +50 | |
| Rated life hours | 35,000-50,000H | |
| LED chip | COB | |





| SCOPE PRO | 030833A01(Pre-embedded) | |
|-----------------------|-------------------------------|--|
| Power | 20W | |
| Beam angle | 15°/23°/36° | |
| Color temperature | 2700K/3000K/3500K/4000K/5000K | |
| Light efficiency | 75lm/W | |
| Color rendering index | ≥90 | |
| Operating temperature | -25- +50 | |
| Rated life hours | 35,000-50,000H | |
| LED chip | COB | |



| SCOPE PRO | 030833A02(Pre-embedded) | |
|-----------------------|-------------------------------|--|
| Power | 40W | |
| Beam angle | 15°/23°/36° | |
| Color temperature | 2700K/3000K/3500K/4000K/5000K | |
| Light efficiency | 77lm/W | |
| Color rendering index | ≥90 | |
| Operating temperature | -25- +50 | |
| Rated life hours | 35,000-50,000H | |
| LED chip | COB | |





| OPTIONS | |
|---------|-----------|
| 1 | NO DIM |
| 2 | DIM 1-10V |
| 3 | DIM DALI |
| 4 | TRIAC |



COLOUR | BK ■ WH □ | MATERIAL | AL

| OPTIONS | |
|---------|-----------|
| 1 | NO DIM |
| 2 | DIM 1-10V |
| 3 | DIM DALI |
| 4 | TRIAC |



COLOUR | BK ■ WH □ | MATERIAL | AL