




UFO



| | |
|-----------------------|-------------------------------------|
| UFO | 01.195A30000 |
| Power | 25W |
| Beam angle | 12°/20° |
| Color temperature | 2700K/3000K/3500K/4000K/2700K-6000K |
| Light efficiency | 80lm/W |
| Color rendering index | ≥90 |
| Operating temperature | -25-50°C |
| Rated life hours | 35,000-50,000H LM80 |
| LED chip | SMD |



| | |
|-----------------------|-------------------------------------|
| UFO | 01.195A60000 |
| Power | 50W |
| Beam angle | 12°/20° |
| Color temperature | 2700K/3000K/3500K/4000K/2700K-6000K |
| Light efficiency | 80lm/W |
| Color rendering index | ≥90 |
| Operating temperature | -25-50°C |
| Rated life hours | 35,000-50,000H LM80 |
| LED chip | SMD |






| | |
|-----------------------|-------------------------------------|
| UFO | 01.195A90000 |
| Power | 75W |
| Beam angle | 12°/20° |
| Color temperature | 2700K/3000K/3500K/4000K/2700K-6000K |
| Light efficiency | 80lm/W |
| Color rendering index | ≥90 |
| Operating temperature | -25-50°C |
| Rated life hours | 35,000-50,000H LM80 |
| LED chip | SMD |



OPTIONS

| | |
|---|---------|
| 1 | Non-DIM |
| 2 | TRIAC |
| 3 | 0/1-10V |
| 4 | DALI |
| 5 | BLE |
| 6 | ZIGBEE |



COLOUR | WH+BK | MATERIAL | AL |